



ELECTRICAL PROPERTIES

- | | |
|--|-------|
| 1. Max. operating voltage | 69kV |
| 2. Lightning Impulse Withstand Voltage | 325kV |
| 3. Power Frequency Withstand Voltage (wet) | 140kV |

PHYSICAL PROPERTIES

- | | |
|---------------------------|--------------------|
| 1. Min. Creepage Distance | 1300mm |
| 2. Arcing Distance | 600mm |
| 3. Portland cement | 52.5 |
| 4. Material of fitting | Galv. ductile iron |

MECHANICAL PROPERTIES

- | | |
|-----------------------|-------|
| 1. Bending Strength | 10kN |
| 2. Torsional Strength | 4kN.m |

According to Standard: IEC 60168 & IEC 60273

Quote (mm) senza indicazione di tolleranza secondo UNI EN 22768-1 grado: <input type="checkbox"/> Fine <input checked="" type="checkbox"/> Media <input type="checkbox"/> Grossolana <input type="checkbox"/> Molto grossolana		Quote (mm) without any tolerance indication are according to UNI EN 22768-1 std's: <input type="checkbox"/> Fine <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Coarse <input type="checkbox"/> Very coarse	
Disegno di proprietà della ISOLEX che si riserva tutti i diritti di legge / All rights pertaining to this drawing are reserved for ISOLEX			
Cliente Customer	N. Ordine P. Order	Scala Scale 1:1	Codice Code C10-325-1300
Conferma Acknowledg.		File	Revisione Revision 1 A4
		Foglio Sheet 1 di 1 of 1	
		Disegno N. - Dwg. No. ID10320	
Descrizione - Description		Ceramic post insulator	