



Material: L2561 aluminum alloy

Colour	Brown glaze Porcelain
Nominale creepage distance	670 mm
Bending breaking load not less than	4 kN
All other requirements shall comply with the provisions of GB8287.1-89	

**MODIFICHE**  
 0 I.C.0001  
 23-01-25  
 AT

Quote (mm) senza indicazione di tolleranza secondo UNI EN 22768-1 grado: <input type="checkbox"/> Fine <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Coarse <input type="checkbox"/> Molto grossolana Quotes (mm) without any tolerance indication are according to UNI EN 22768-1 std's: <input type="checkbox"/> Fine <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Coarse <input type="checkbox"/> Very coarse		Disegno di proprietà della ISOLEX che si riserva tutti i diritti di legge / All rights pertaining to this drawing are reserved for ISOLEX	
Cliente Customer	N. Ordine P. Order	Scala Scale 1:1	Codice Code
Confirma Acknowledg.	ISOLEX Milano Italy	File	Revisions Revision - A4
Descrizione - Description Porcelain Indoor Post insulator G-300-670			Foglio Sheet 1 of 1 Disegno N. - Dwg. No. ID10457

ACAD