


Top & Bottom View



Sheds

1	Material	Porcelain
ITEM No.	DESCRIPTION	MATERIALS QTY REMARK

TECHNICAL REQUIREMENTS /CARATTERISTICHE TECNICHE		
ELECTRICAL PROPERTIES/PROPRIETA ELETTRICHE		
Lighting Impulse Withstand Voltage	kV	125
Power Frequency Withstand voltage (wet)	kV	50
PHYSICAL PROPERTIES/PROPRIETA FISICHE		
Creepage distance min.	mm	600
Color	Brown	
Metallic Material	Galv.cast Iron	
MECHANICAL PROPERTIES/PROPRIETA MECCANICHE		
Cantilever Strenght	kN	4
Torsion strenght	kN/m	0.8
Applicable standard	IEC 60168 & IEC 60273	

Quote (mm) senza indicazione di tolleranza secondo UNI EN 22768-1 grado: Fine Medium Coarse Molto grossolana
 Quotes (mm) without any tolerance indication are according to UNI EN 22768-1 std's: Fine Medium Coarse Very coarse

Disegno di proprieta della ISOLEX che si riserva tutti i diritti di legge / All rights pertaining to this drawing are reserved for ISOLEX

N. Ordine P. Order	Data Date	Disegnato Drawn	AT	Data Date	08/07/24	Scala Scale	1:1	
Cliente Customer	Data Date	Approvato Approved	RIZZI	Data Date	08/07/24	Revisions Revision	1 2 3 4 5 6	
Conferma Acknowledg.	-	Controllato Checked		File Disk	ID10494	Codice Code	TABLE	A4

ISOLEX
Milano Italy

Descrizione - Description: Post insulator C4-125 III

Foglio Sheet 1 di of 1
Disegno N. - Dwg. No. ID10494

01	-	-	--/--/--	
Rev.	Disegnato Drawn	Approvato Approved	Data Date	Descrizione Description