



TECHNICAL REQUIREMENTS /CARATTERISTICHE TECNICHE

ELECTRICAL PROPERTIES/PROPRIETA ELETTRICHE

Lightning Impulse Withstand Voltage (dry)	kV	125
Power Frequency Withstand Voltage (dry)	kV	68/1min
Rated Voltage	kV	24
Rated Current	A	1250
Partial discharge	<100 pC at 25,2 kV 5 pC at 15,3 kV	

MECHANICAL PROPERTIES/PROPRIETA MECCANICHE

Bending min.	kN	7,5
Applicable standard / Standard applicabili	IEC 60137	
Minimum temperature range between	-20°C and +75°C	

4	Conductive rod	Copper rod
3	Colour	Red RAL 3011
2	Material	Epoxy Resin
1	Weight	10,5 kg
ITEM No.	DESCRIPTION	MATERIALS QTY REMARK

Quote (mm) senza indicazione di tolleranza secondo UNI EN 22768-1 grado: <input type="checkbox"/> Fine <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Coarse <input type="checkbox"/> Molto grossolana			
Quotes (mm) without any tolerance indication are according to UNI EN 22768-1 std's: <input type="checkbox"/> Fine <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Coarse <input type="checkbox"/> Very coarse			
Disegno di proprietà della ISOLEX che si riserva tutti i diritti di legge / All rights pertaining to this drawing are reserved for ISOLEX			
N. Ordine P. Order	Data Date	Disegnato Drawn	AT
		Data Date	27/03/26
Cliente Customer	Data Date	Approvato Approved	RIZZI
		Data Date	27/03/26
Conferma Acknowledg.	Controllato Checked	File Disk	ID10516
		Codice Code	TABLE
Descrizione - Description			Foglio Sheet
Wall bushing 24 kV 1250 A			1 di 1 of 1
			Disegno N. - Dwg. No. ID10516

01	-	-	--/--/--	
Rev.	Disegnato Drawn	Approvato Approved	Data Date	Descrizione Description